

NT 65/2 Ap

Powerful, twin-motor wet & dry vacuum for professional applications. Featuring the Ap semi-automatic filter clean system for constantly high suction power.

1 On-board practical storage

- Large on-board storage area for tool and accessory storage.

2 Integrated drain hose (oil-resistant)

- Easily accessible drain hose for convenient liquid disposal.

3 ApClean (semi-automatic filter cleaning system)

- The free filter means that the user can work for long intervals without interruption.
- Optimal suction power with high efficiency.

4 Hose and bend attachment

- Convenient suction hose and bend attachment for easy transport and storage.



Page 2
 5.Object
 page6177186904282_std_1_272x272px.jpg
 wurde anstatt
 PAGE6177186904282_std_1_272x272px.JPG
 platziert.
 6 Object
 page6177182885753_std_1_272x272px.jpg
 wurde anstatt
 PAGE6177182885753_std_0_272x272px.JPG
 platziert.

NT 65/2 Ap

- Semi-automatic filter cleaning system
- Flat pleated filter (dust class M)
- Drain hose and push handle

Technical data

Order no.		1.667-297.0
EAN code		4039784727342
Current type	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s	2 x 74
Vacuum	mbar / kPa	254 / 25,4
Container content	l	65
Container material		Plastic
Rated input power	W	max. 2760
Standard nominal size		DN 40
Cable length	m	10
Sound pressure level	dB(A)	73
Quantity of motors		2
Weight	kg	20
Dimensions (L x W x H)	mm	567 x 482 x 920

Equipment

Suction hose	m	4 / with bend	Safety class	II
Suction Tube	piece(s) x m	2 x 0,5 / Metal	Caster with brake	■
Filter bag		Paper		
Wet and dry floor tool	mm	360		
Crevice nozzle		■		
Drain hose (oil-resistant)		■		
Auto shutdown when max. level is reached		■		
Flat pleated filter		Paper		
Filter cleaning		ApClean (semi-automatic filter cleaning system)		
Sturdy bumper		■		
Push handle		■		

■ Included in delivery.

NT 65/2 AP 1.667-297.0


KÄRCHER




1



2



3



4



5

		Order no.	Quantity				Price	Description	
Flat pleated filter (paper)									
Flat pleated filter	1	6.904-283.0	1 piece(s)					Paper, dust class M (also NT 65/2 Ap opt. for NT 75/2 Ap Me Tc models).	■
Flat pleated filter HEPA, dust class H									
HEPA surface filter	2	6.904-364.0	1 piece(s)					HEPA surface filter, dust class H (H 14).	□
Flat pleated filter (PES)									
Flat filters (PES)	3	6.904-284.0	1 piece(s)					Polyester fleece, rot-proof, dust class M. (Also for NT 65/2 AP Me Tc and NT 72/2 Ap Me Tc).	□
Special filter bags, wet filter bags									
Special filter bags, wet filter bags	4	6.904-252.0	5 piece(s)						□
Plastic sacks for dust-free disposal									
Plastic bag for dust-free disposal	5	6.900-698.0	10 piece(s)					PE plastic sack. Plastic sacks for dust-free disposal.	□
Membrane filter / fabric filter									
Membrane filter	6	6.904-282.0	1 piece(s)					Polyester needle fleece, dust class M, washable (40 °C). Not suitable for dust class H.	□
Fleece filter bags (3 ply)									
Fleece filter bags	7	2.885-753.0	5 piece(s)						□

■ Included in delivery. □ Available accessories.

Page 2

540 Object

page6177216903035_

std_1_272x272px.jpg kon-

werde anplaziert werden.

PA 058477214440679_

page6177216903035_

plazier_272x272px.jpg kon-

610 Object plaziert werden.

page6177212889141_

page6177216903035_

std_1_272x272px.jpg

R0458477214440679_

std_1_272x272px.JPG

plazier_272x272px.jpg

page6177216903035_

page6177216903035_

std_1_272x272px.jpg

konnte nicht anplaziert

werden anstatt

2-4

13

		Order no.	Quantity	ID	Length	Width	Price	Description	
Plastic bend									
Elbow packaged NW40 1K	1	2.889-171.0	1 piece(s)	DN 40					■
Plastic bend	2	5.031-718.0	1 piece(s)	DN 35				Plastic with C-35 clip system.	□
	3	5.031-939.0	1 piece(s)	DN 35				Plastic ID 35 with C-35 clip system, electrically conductive.	□
	4	5.032-427.0	1 piece(s)	DN 40				Plastic with C-40 clip system, electrically conductive.	□
Elbow electrically conducting packaged N	5	2.889-148.0	1 piece(s)	DN 35					□
All-purpose nozzles (wet/dry)									
Floor tool packaged NW40 360mm	6	2.889-153.0	1 piece(s)	40		360 mm			■
Floor tool DN40-370	7	6.903-018.0	1 piece(s)	40		370 mm		Aluminium with height-adjustable rollers, brush strips (6.903-064.0) and squeegees (6.903-081.0, oil-resistant).	□
Floor tool neutrally DN40	8	6.906-383.0	1 piece(s)	40		450 mm		Aluminium with height adjustable rollers, brush strips (6.903-065.0) and squeegees (6.906-146.0).	□
Floor tool neutrally DN35	9	6.906-384.0	1 piece(s)	35		370 mm		Aluminium with height adjustable rollers, brush strips (6.903-064.0), squeegees (6.903-081.0, oil-resistant).	□
Wet and dry floor nozzle	10	2.889-117.0	1 piece(s)	40		400 mm			□
Crevice nozzles									
Crevice nozzle DN 40 300mm 1:50	11	5.130-655.0	1 piece(s)	DN 40					■
Crevice nozzle DN35	12	6.900-385.0	1 piece(s)	DN 35	210 mm			Plastic.	□
Crevice nozzle	13	6.900-922.0	1 piece(s)	35	500 mm			Metal.	□
Crevice nozzle DN40	14	6.905-817.0	1 piece(s)	40	400 mm				□
Suction tubes stainless steel									
Set suction tube stainless steel NW40 55	15	2.889-194.0	2 piece(s)	40	550 mm				■
Suction tube, ID 40	16	6.902-081.0	1 piece(s)	40	500 mm			For use in wet, damp environments or for wet vacuuming.	□
Suction tube	17	6.906-531.0	1 piece(s)	40	1000 mm				□
Suction tube, DN 35	18	6.902-154.0	1 piece(s)	35	500 mm			Mainly for wet vacuuming or vacuuming corrosive media.	□
Bend stainless									
Bend, stainless steel ID 35	19	6.903-141.0	1 piece(s)	DN 35				Stainless steel.	□
Bend, stainless steel ID 40	20	6.902-079.0	1 piece(s)	DN 40					□
Bend metal									
Bend, DN 35, metal	21	6.900-519.0	1 piece(s)	DN 35				Metal, ID 35.	□
Bend, DN 40, metal	22	6.900-276.0	1 piece(s)	DN 40				Metal, ID 40.	□
All-purpose brushes									
All-purpose brush	23	6.903-863.0	1 piece(s)	35	120 mm			Natural bristles (ox hair), bristle element 120 x 45 mm, ID 35.	□
Car cleaning nozzles									
Car nozzle	24	6.900-952.0	1 piece(s)	DN 40		90 mm		Plastic.	□
Rubber suction tools, nose 45°									
Rubber suction tools, nose 45°	25	6.902-104.0	1 piece(s)	35	220 mm			For vacuuming machines, oil-resistant.	□
	26	6.902-105.0	1 piece(s)	40	220 mm			For vacuuming machinery, oil-resistant.	□
Pipe dusting nozzles									
BRUSH	27	6.903-035.0	1 piece(s)	35				Plastic, tube diameter 100 mm.	□
	28	6.903-036.0	1 piece(s)	35				Plastic, tube diameter 200 mm.	□
Suction brushes									
Suction brush DN35	29	6.903-862.0	1 piece(s)	35		70 mm		Natural bristles (cow hair), rotatable.	□
Suction tubes metal									
Suction tube DN35	30	6.900-514.0	1 piece(s)	35	500 mm			Metal, chromium-plated.	□

■ Included in delivery. □ Available accessories.

NT 65/2 AP 1.667-297.0

KÄRCHER



		Order no.	Quantity	ID	Length	Price	Description	
Suction hoses complete (Clip-system)								
Suction hose	1	2.889-138.0	1 piece(s)	DN 40	4 m			■
	2	4.440-678.0	1 piece(s)	DN 40	4 m		With bend, C DN-40.	□
Suction hose, complete (clip system), C DN 40, 4 m	3	4.440-679.0	1 piece(s)	DN 40	4 m		With bend and module (4.060-474.0).	□
Suction hose complete (Clip-system), C ID 40, 4 m, el.	4	4.440-728.0	1 piece(s)	DN 40	4 m		With bend and module (4.060-533.0), electrically conductive.	□
Electrically conductive suction hose	5	2.889-137.0	1 piece(s)	DN 35	4 m			□
Suction hose	6	2.889-139.0	1 piece(s)	DN 40	2,5 m			□
Suction hose, oil-resistant	7	2.889-140.0	1 piece(s)	DN 40	4 m			□
Electrically conductive suction hose	8	2.889-141.0	1 piece(s)	DN 40	4 m			□
	9	2.889-142.0	1 piece(s)	DN 40	2,5 m			□
Repair kits								
Repair set, C 40	10	2.639-873.0	1 piece(s)	C- 40			Suction hose repair kit (clip system).	□
Repair kit ID 61	11	2.862-038.0	1 piece(s)	DN 61			Suction hose repair kit.	□
Repair set NW40	12	2.889-150.0	1 piece(s)	DN 40				□
Suction hoses (Clip-system)								
Suction hose (clip system), C 40, 10 m	13	6.906-279.0	1 piece(s)	DN 40	10 m		With bayonet and clip connection, C 45	□
Suction hose	14	6.906-321.0	1 piece(s)	40	4 m		With bayonet and clip connection, C 40.	□
	15	6.906-714.0	1 piece(s)	DN 40	4 m		With bayonet and clip connection, C 45.	□
Suction hose (Clip-system), C 40, 16 m	16	6.906-635.0	1 piece(s)	DN 40	16 m		With bayonet and clip connection, C 40	□
Suction hose (clip system), C 40, 10 m, el.	17	6.906-877.0	1 piece(s)	DN 40	10 m		With bayonet and clip connection, electrically conductive, C 40	□
Suction hoses complete								
Suction hose, complete	18	4.440-264.0	1 piece(s)	DN 61	4 m		Plastic, EVA	□
Suction hose complete, ID 61, smooth inside	19	4.440-328.0	1 piece(s)	DN 61	3 m		Industrial hose, PVC / elastomer with steel spiral, smooth inside.	□
Suction hose complete, DN 61, 10 m	20	4.440-467.0	1 piece(s)	DN 61	10 m		Plastic, EVA	□
Suction hose complete, ID 61, 4 m, oil-resistant	21	4.440-613.0	1 piece(s)	DN 61	4 m		Oil-resistant.	□
Suction hose complete, ID 61, 4 m, el.	22	4.440-616.0	1 piece(s)	DN 61	4 m		Electrically conductive.	□
Suction hose, complete	23	4.440-263.0	1 piece(s)	DN 40	4 m		Standard, plastic.	□
Suction hose complete, ID 40, 4 m, oil-resistant,	24	4.440-303.0	1 piece(s)	DN 40	4 m		Oil-resistant.	□
Suction hose, complete	25	4.440-463.0	1 piece(s)	DN 40	10 m		Standard, plastic.	□
Suction hose complete	26	4.440-466.0	1 piece(s)	DN 40	10 m		Electrically conductive, plastic.	□
Suction hose complete, ID 40, 10 m, oil-resistant	27	4.440-612.0	1 piece(s)	DN 40	10 m		Oil-resistant.	□
Hose connection								
Adapter, DN 32/35, with internal thread	28	6.902-077.0	1 piece(s)	DN 32			For connecting 2 suction hoses (not ESB 28 and 34).	□
Adapter, DN 40 with internal thread	29	6.900-286.0	1 piece(s)	DN 40			For connecting 2 suction hoses, threaded at both ends.	□
Extension hoses (Clip-system)								
Extension hose, C 40	30	6.906-344.0	1 piece(s)	DN 40	2,5 m		For all C-40 hoses.	□

■ Included in delivery. □ Available accessories.

NT 65/2 AP
1.667-297.0



Page 2
0.Object
page6177212889146_
std_01_272x272px.jpg
wurde anstatt
PAGE6177212889138_
std_01_272x272px.JPG
plaziert.¹



		Order no.	Quantity	ID	Length		Price	Description	
Extension hose packaged NW40 2.5m	31	2.889-146.0	1 piece(s)	DN 40	2,5 m				☐

■ Included in delivery. □ Available accessories.

NT 65/2 AP 1.667-297.0

KÄRCHER



		Order no.	Flow Rate	Water feed temperature	Length	Length	Price	Description	
Telescopic									
Telescopic lance TL 10 H	1	4.762-611.0		max. 60 °C				Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	☐
Telescopic lance TL 10 C	2	4.762-612.0		max. 60 °C				Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	☐
TL vacuum cleaner adapter	3	9.751-306.0						TL suction cup for 10 and 14 m long telescopic lances comprising suction bend connection (DN 35, DN 40) and connection for the suction nozzles.	☐

■ Included in delivery. □ Available accessories.

Page 2

14.Object
page6177206902072_272x272px.jpg kon-
nte nicht plziert werden.
15.Object
page6177202860117_272x272px.jpg kon-
nte nicht plziert werden.



10

11, 13

		Order no.	Quantity	ID			Price	Description	
Y-adapter kit									
Y-adapter kit	1	2.637-217.0	1 piece(s)	35				Distributor, plastic.	☐
Connecting sleeve C-DN (clip on taper), EL (electroconductive)									
C-ID 35 adapter	2	5.407-112.0	1 piece(s)	35				C 35 hose connector for ID 35 accessory, electrically conductive.	☐
C 40 adapter	3	5.407-109.0	1 piece(s)	C-DN 40				C 40 hose connector for ID 35 accessory, electrically conductive.	☐
C-DN 40 adapter	4	5.407-111.0	1 piece(s)	40				C 40 hose connector for DN 40 accessory, electrically conductive.	☐
Connection cone NW35	5	5.407-005.0							☐
Connection cone NW40	6	5.407-006.0		DN 40					☐
Adapter for electric power tools, clip on, el.									
Sleeve for tool C35EL	7	5.453-042.0	1 piece(s)	35				Plastic, adjustable from DN 26-36 (Te/Eco M/H), electrically conductive.	☐
Adapter for electric power tools, C 35, el.	8	5.453-048.0	1 piece(s)	35				Inside Ø 25.4 mm, outside Ø 34.6 mm / 38 mm, electrically conductive.	☐
	9	5.453-050.0	1 piece(s)	35				Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive.	☐
Adapter for electric power tools, screwable									
Power tool adapter, threaded, DN 35	10	5.453-016.0	1 piece(s)	35				Plastic, adjustable from DN 26-36.	☐
Adapter for electric power tools, screwable, ID 35	11	5.453-026.0	1 piece(s)	35				Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	☐
Power tool adapter, threaded, DN 35	12	6.902-059.0	1 piece(s)	35				Inside Ø 32 mm, outside Ø 39 mm.	☐
	13	6.902-095.0	1 piece(s)	35				Inside Ø 28 mm, outside Ø 34/38.8 mm, electrically conductive.	☐
Adapter (tube -> nozzle)									
Adapter	14	5.453-019.0	1 piece(s)	40				From ID 40 to 61, plastic.	☐
Reducing sleeves									
Reducer	15	5.407-108.0	1 piece(s)	40				C-40 hose with 35 external thread for threaded adapter, DN 35.	☐
Sleeve C40 / C35	16	5.407-113.0	1 piece(s)	40				Reducer from C-40 clip to C-35 clip.	☐
Reducer (tube -> nozzle)									
Reducer	17	6.902-017.0	1 piece(s)	40				From ID 40 to ID 35, plastic.	☐
Reducer from ID 35 to 32	18	6.902-072.0	1 piece(s)	35				From ID 35 to 32, metal.	☐
Set reducing / extension sleeves									
Set reducing / extension sleeves	19	2.860-117.0	1 piece(s)					ID 40/35, ID 35/32 (tube -> nozzle), plastic.	☐

■ Included in delivery. □ Available accessories.

NT 65/2 AP
1.667-297.0



		Order no.	ID					Price	Description
Target group specific vacuum cleaner accessory sets									
Professional cleaning kit ID 40	1	2.637-353.0	DN 40						Professional cleaning kit ☐
Car cleaning kit	2	2.862-166.0	DN 35						Car cleaning kit ☐
Chip cleaning kit	3	2.640-760.0	DN 61						Chip cleaning kit ☐

■ Included in delivery. □ Available accessories.

NT 65/2 AP
1.667-297.0



		Order no.	Quantity	Width			Price	Description	
Other									
CS 40 Me	1	2.863-026.0	1 piece(s)						☐
Adapter connection old elektr. leitend	2	5.031-436.0							☐

■ Included in delivery. ☐ Available accessories.

NT 65/2 AP
1.667-297.0



		Order no.	Quantity	ID	Length	Width	Price	Description	
UBS non-conductive media									
Add-on kit nonconducting media NT Tact ²	1	2.642-602.0	1 piece(s)					For switching off when vacuuming non-conductive fluids such as oils and greases	☐

■ Included in delivery. ☐ Available accessories.